



ADAM TECH Cable Assembly

Adam Tech launches standard Cable Assembly items for the increasing inquiries, along with original quality connectors to provide total solution and service. Customers now can pick up specific board side connectors with necessary cables in one click to their door steps.

To ease up engineering process toward complete connections, selected quality cables with dedicated plugs could come in handy and save the day. Start with USB 2.0 to USB TYPE-C conversion cables, Ethernet Cat5e, Cat6 network patch cables, USB 2.0, USB 3.0 Type A/B M/F extension cables, HDMI 1.4 extension cables, VGA extension cables and Mini Display Port to HDMI, DVI and VGA conversion cables in most asked lengths.



[CA-USB-AM-CM-XFT.pdf](#)
USB2.0 AM TO USB TYPE-C
L=1FT, 3FT

Plugs: P1= USB Connector 2.0 A Type Plug, P2= USB Connector 3.1 C Type Plug
Cable: UL type,
7/0.12TA*1P+7/0.12TA*2C+AL+BD48/0.10TCCS,
OD=3.8+/-0.10mm



[NPC-5E-XXX-XX.pdf](#)
[NPC-6-XXX-XX.pdf](#)
CAT 5E, CAT6 RJ45 8P8C TO
RJ45 8P8C, LENGTH: 3, 7, 10
FEET, COLOR: BLUE, NO BOOT

Plugs: P1 & P2: RJ45, 8P8C, CAT 5e Plug, UL94V-0,
Gold plated.
Cable: Cat 5e, UTP 24 AWG x 4P, O.D.: 5.4mm +/-
0.2mm, UL, cUL, & ETL verified



[NPC-5E-XXX-XX-BB.pdf](#)
[NPC-6-XXX-XX-BB.pdf](#)
CAT 5E, CAT 6 RJ45 8P8C TO
RJ45 8P8C, LENGTH: 3, 7, 10
FEET, COLOR: BLUE, BUBBLE
BOOT

Plugs: P1 & P2: RJ45, 8P8C, CAT 6 Plug, UL94V-0,
Gold plated.
Cable: Cat 6, UTP 24 AWG x 4P, O.D. 5.9mm +/-
0.15mm, UL & ETL verified, conforms to ANSI/TIA-
568-C.2



[CA-USB3-AM-BM-XFT.pdf](#)
USB 3.0 CABLE, A MALE
TO B MALE, BLUE, 3, 6, 10
FT.

Plugs: P1= USB Connector 3.0 A Type Plug, Gold
Flash Plated, P2= USB Connector 3.0 B Type Plug,
Gold Flash Plated
Cable: UL20276,
(30#*1P+D+A+M)*2C+30#*1P+26#*2C+A+B,
OD: .189" (4.8mm)



[CA-USB3-AM-AF-XFT.pdf](#)
USB 3.0 CABLE, A MALE
TO A FEMALE, BLUE, 3, 6,
10 FT.

Plugs: P1= USB Connector 3.0 A Type Plug, Gold
Flash Plated, P2= USB Connector 3.0 A Type Socket,
Gold Flash Plated
Cable: UL20276,
(30#*1P+D+A+M)*2C+30#*1P+26#*2C+A+B,
OD: .189" (4.8mm)



[CA-USB-AM-BM-XFT.pdf](#)
USB 2.0 CABLE, A MALE TO
B MALE, BLACK, 3, 6, 10 FT.

Plugs: P1= USB Connector 2.0 A Type Plug, P2=
USB Connector 2.0 B Type Plug
Cable: UL2725, (1P+2C)+A+B, OD=.189" (4.8mm)



[CA-USB-AM-AF-XFT.pdf](#)
USB 2.0 CABLE, A MALE TO
A FEMALE, BLACK, 3, 6, 10
FT.

Plugs: P1= USB Connector 2.0 A Type Plug, P2=
USB Connector 2.0 A Type Socket
Cable: UL2725, (1P+2C)+A+B, OD=.189" (4.8mm)



[CA-USB-AM-AM-XFT.pdf](#)
USB 2.0 CABLE, A MALE TO
A MALE, BLACK, 3, 6, 10 FT.

Plugs: P1=P2= USB Connector 2.0 A Type Plug
Cable: UL2725, (1P+2C)+A+B, OD=.189" (4.8mm)



[CA-VGA-M-M-XFT.pdf](#)
VGA CABLE, HD15 MALE TO
HD15 MALE, EMI, 3, 6, 10 FT.

Connector: P1=P2= D-Sub Connector 15P
Cable: UL2919, 28/28-3C/9+A=D+B, OD: .315"
(8mm)



[CA-MINIDP-HDMIF-XFT.pdf](#)
MINI DISPLAY PORT MALE
TO HDMI female, 3, 6, 10 FT.

Connector: P1= HDMI A Type Socket, , w/PCB board.
P2=Mini Display Port Plug,
Cable: UL20276,
(32#*1P+ADM)*5C+32#*3C+28#*2C+A+B,
OD: .217" (5.5mm)



[CA-MINIDP-DVIM-XFT.pdf](#)
MINI DISPLAY PORT MALE
TO DVI MALE, 3, 6, 10 FT.

Connector: P1= DVI-D 24P Plug, w/PCB board.
P2=Mini Display Port Plug,
Cable: UL20276,
(32#*1P+ADM)*5C+32#*3C+28#*2C+A+B, OD: .217"
(5.5mm)



[CA-MINIDP-VGAF-XFT.pdf](#)
MINI DISPLAY PORT MALE
TO VGA FEMALE, 3, 6, 10 FT.

Connector: P1= D-Sub connector, Socket, 15P, VGA,
w/PCB board. P2=Mini Display Port Plug,
Cable: UL20276,
(32#*1P+ADM)*5C+32#*3C+28#*2C+A+B, OD: .217"
(5.5mm)



[CA-HDMI-AM-AM-XFT.pdf](#)
HDMI 1.4 HDMI 19P A
PLUG/HDMI 19P A PLUG,
color: BLACK, 3, 6, 10 FT.

Plugs: P1=P2= HDMI A Type Plug
Cable: UL20276,
[(30#*1P+D+A+M)*5C+30#*4C]+A+D+B, OD: .236"
(6mm)

Electrical Test: All Assemblies must be 100% Tested for Shorts, Open, Continuity, and Physical Appearance.
Environment: Lead free, RoHS compliant